



**DMC 164-F AND DMC 164-C**



AVAILABLE WITH OR WITHOUT CLIP



NOTE: LINE DRAWINGS MAY NOT BE TO SCALE.

**DMC 123-F AND DMC 123-C**



AVAILABLE WITH OR WITHOUT CLIP



NOTE: LINE DRAWINGS MAY NOT BE TO SCALE.

**PRODUCT FEATURES**

- No-clip panel, or clip installation for expansion/contraction
- Panel depths of  $\frac{7}{8}$ "
- Cost-effective installation
- Horizontal or vertical installation
- Panel lengths:
  - 30' maximum for steel
  - 22' maximum for aluminum on the thru-fastened leg; longer lengths available on clip panels

**MATERIAL COLOR OPTIONS**

- 43 stocked colors (24 gauge steel)

- 36 stocked colors (.032 aluminum)
- 16 stocked colors (22 gauge steel)
- 22 stocked colors (.040 aluminum)
- 29 stocked colors (.050 aluminum)
- Drexlume™ available

**TESTING**

DMC 164-F and 164-C;

- ASTM E330
  - 24 Ga. Steel
  - 22 Ga. Steel
  - .032 Aluminum
  - .040 Aluminum

- ASTM E 283-04
- ASTM E 331-00
- AAMA 501.1-05

**MATERIAL SUBSTRATES**

- .032 aluminum
- .040 aluminum
- .050 aluminum
- 24 gauge steel
- 22 gauge steel

**SPECS**

- 12" or 16" Wide
- $\frac{7}{8}$ " High