

# SECURE LOK FASCIA



*The Drexel Metals Secure Lok Fascia System is a three-part assembly that includes a continuous cleat, 6" spring clip and a decorative fascia cover for single-ply commercial roof systems. Our Secure Lok Fascia is available in prepainted Kynar 500® .040" & .050" formed aluminum and as 22 & 24 gauge Galvalume® steel. This product features a 24 gauge pre-punched cleats with fasteners spaced at 12" on center. All products come in standard 10' standard cleat and cover lengths. Concealed splice plates and fasteners are included with the purchase of this product.*

## FEATURES AND BENEFITS

- Secures roof Membrane to Parapet Wall
- Allows for the use of high-torque screws without penetrating the top surface of the membrane
- Pre-Punched Continuous Cleat
- ANSI-SPRI ES-1 Certified
- Corporate and Custom Colors are available
- Gold Standard Paint Warranty

## INSTALLATION

For complete installation instructions, please refer to Drexel Metals Architectural specifications and details.

REVIEW CURRENT DREXEL METALS ARCHITECTURAL SPECIFICATION AND DETAILS FOR SPECIFIC INSTALLATION REQUIREMENTS.

## QUALITY ASSURANCE

Drexel Metals Secure Lok Fascia system is tested per ANSI/SPRI Test Method RE-2 for fascia. The Fascia systems shall be certified by Drexel Metals to design pressures as indicated in current edition of SPRI's Wind Resistance Standard for Edge Systems used with Low Slope Roofing System. This products meets International Building Code minimum requirement.

## TECHNICAL SERVICES

Engineering and shop drawings, as well as longform specifications and CAD details, are available from Drexel Metals. Product samples, detail sheets, color chips and color charts are also available for submittal packages. For personal assistance with questions or for full submittals, contact Drexel Metals or your local independent sales representative.

## PRODUCT SPECIFICATIONS

Material	Face	Sustained Pressures
24 gauge	up to 8.25"	200 psf*
.040 AL	up to 8.25"	210 psf*
22 gauge	up to 12.75"	150 psf*
.050 AL	up to 12.75"	150 psf*

\*Design Engineer must apply the Factor of Safety

\*\*ADDITIONAL GAUGES - .063 aluminum are available upon request