# **ECONO GRAVEL STOP**



The Drexel Metals Econo Gravel Stop System is a two-part assembly that includes a continuous cleat and a decorative fascia cover for single-ply commercial roof systems. Our Econo Gravel Stop is available in pre-painted Kynar 500°.040″ formed aluminum as well as 24 gauge Galvalume° steel. This product features a 24 gauge pre-punched cleats with fasteners spaced at 12″ on center. All products come in standard 10′ standard cleat and fascia cover lengths. Concealed splice plates and fasteners are included with the purchase of this product.



## **FEATURES AND BENEFITS**

- · Secures roof Membrane to Parapet Wall
- Allows for the use of high-torque screws without penetrating the top surface of the Membrane
- · Pre-Punched Continuous Cleat
- · Economical Design
- · ANSI-SPRI ES-1 Certified
- · 90 mph/20 year Wind Warranty
- · 35 Year Gold Standard Paint Warranty
- · Corporate and Custom Colors are available

#### **INSTALLATION**

For complete installation instructions, please refer to Drexel Metals Architectural specifications and details.

REVIEW CURRENT DREXEL METALS ARCHITECTURAL SPECIFICATION AND DETAILS FOR SPECIFIC INSTALLATION REQUIREMENTS.

## **QUALITY ASSURANCE**

Tested in accordance with ANSI/SPRI/FM4435/ES-1 Test Standard For Edge Systems Used With Low Slope Roofing Systems to comply with the International Building Code.

#### **TECHNICAL SERVICES**

Engineering and shop drawings, as well as long- form specifications and CAD details, are available from Drexel Metals. Product samples, detail sheets, color chips and color charts are also available for submittal packages. For personal assistance with questions or for full submittals, contact Drexel Metals or your local independent sales representative.

### **PRODUCT SPECIFICATIONS**

Material	Face	Sustained Pressures
24 gauge	up to 7"	-70 psf (*)
.040 AL	up to 7"	-90 psf (*)

<sup>\*</sup>Design Engineer must apply the Factor of Safety

<sup>\*\*</sup>ADDITIONAL GAUGES - .050 and .063 aluminum and 22 gauge Galvalume are available upon request