

DMC 150NS PROFILE



PANEL DETAILS

STANDARD PANEL WIDTHS

15", 19"

Drexel Metals design pressures, wind uplifts and test reports are for specific deck attachments, material gauges, clip spacing and panel widths. A complete specification and listing is available online at www.drexelmetals.com


SUBSTRATES AVAILABLE

- Painted Galvalume® - 24ga
- Drexlume™ - 24ga
- Painted Aluminum - .032"

Not seeing the gauge or material you are looking for? Contact your local Drexel Metals representative.

IDEAL APPLICATION RESIDENTIAL

Our DMC 150NS profile offers unlimited design potential with its sleek, crisp appearance and attractive shadow lines. Eliminating the need for metal roof clips, the concealed 1½" self-locking Snap Lock system creates a powerfully protective seal. Versatile and refined, this easy-to-install metal roof delivers superior beauty, durability and strength while showcasing architectural details.




DMC 150NS PROFILE


PROFILE




PANEL RIB OPTIONS




Flat Panel




Clip Relief




Striations




Bead




Small V



Large V



Small Pencil



Large Pencil

Contact your local Drexel Metals representative for specific rib option availability.

PRODUCT INFORMATION

FINISHES

Available in a wide variety of coatings and colors. See the Drexel Metals color charts for standard colors and paint specifications.

PANEL RIB

Factory made or field rolled to exact lengths options

- Flat Panel
- Clip Relief
- Striations
- Bead
- Small and Large V
- Small and Large Pencil

INSTALLATION

Can be installed over plywood decking with approved underlaments. Please see Drexel Metals installation details for complete information.

SLOPE

Minimum slope 2:12

TESTING

- UL 580 Wind Uplift (Class 90)
- UL Environmental - SRI Third Party Verified
- TAS 125 Wind Uplift
- UL 263 Fire Certification
- UL 1897 Extended Phase Wind Uplift
- TAS 100 Wind Driven Rain
- UL 2218 Class 4 Hail Impact
- Miami Dade County Approved
- UL 790 Class A Fire Rating
- Florida Building Code Approved

Testing in accordance with



WARRANTY

35 YEAR WARRANTY - GALVALUME AND ALUMINUM SUBSTRATES

35 year non pro-rated PVDF Paint Warranty

High-performance painted metal roofing product, carefully tensioned leveled for superior flatness.

25 YEAR WARRANTY - DREXLUME SUBSTRATE

Mill finished Galvalume with a two-sided, clear acrylic finish.